

MarkupsList-3.3.1.ods

<b>locomotors</b>	<b>wagons</b>	<b>type</b>	<b>frequency</b>	<b>imply</b>	<b>mandatory wagons</b>	<b>optional wagons</b>	<b>domain</b>	<b>previous</b>	<b>description</b>
<b>antisamy</b>		4	2						present if the Antisamy framework is to be used
<b>appse</b>		3	1						name and version of the application server or servlet container
	<b>arraystring</b>	3	3	<b>+jsp</b>					the list of ArrayList<String> properties of the bean associated with the JSP
<b>bdefmenu</b>		8		<b>indexjsp</b>		<b>bfixedtop</b>			the definition of a navigation bar; it is inside the header.jsp, so it is not valid if Tiles is used
	<b>belong</b>	3		<b>+jsp</b>					element to be displayed in the JSP text
	<b>bfixedtop</b>	4		<b>+bdefmenu</b>					if present, add the navbar-fixed-top clause to the menu
<b>blabel</b>		3	2	<b>bdefmenu</b>	<b>burl</b>				the label of a menu item
	<b>blank</b>	4		<b>+jsp</b>					indicates that you want to open a new tab in the internet browser
	<b>bmenu</b>	8		<b>+jsp, +indexjsp, +userpass</b>					indicates which navigation bar must be contained in the JSP one, or in error.jsp
	<b>boolean</b>	3	3	<b>+jsp</b>					the list of boolean properties of the bean associated with the JSP
	<b>burl</b>	12	3	<b>+blabel</b>					
<b>captc</b>		3	2						presence of a captcha
<b>charset</b>		3	2						Unicode character set; the default is UTF-8
	<b>crud</b>	4		<b>+jsp</b>					the jsp contains a CRUD

MarkupsList-3.3.1.ods

locomotors	wagons	type	frequency	imply	mandatory wagons	optional wagons	domain	previous	description
	cssclass	12	4	+text, +jsp					the invocation of a CSS class, already defined through the odefcss markup
	dao	24		+method, +formn					List of names, separated by commas, of the dao interfaces used within each method (+method) or <b>list-box</b> (+formn); each name must begin with the IRail string and end with the Dao string
company		3	1						company internet domain; e.g.: it.ramecera
defaulan		23	2						default language, i.e. the local language; it must be a code of 2 characters
depen		2	1						group of pre-established dependencies, to be declared in pom.xml
	dress	12		+jsp					the name of the method to add to the JSP bean
edefn		14		ev					<definition name= in tiles.xml
ev		5	2						version of the Tiles framework
	fcartel	3		+formn					name that must appear on the list-box when it is closed
file		20	4						header of a file, markup is immediately followed by the contents of the file
filte		4	2						present if in web.xml filters are to be declared

MarkupsList-3.3.1.ods

locomotors	wagons	type	frequency	imply	mandatory wagons	optional wagons	domain	previous	description
	<b>flabel</b>	3		+formt, +formn, +forma, +formc, +formr					the label of a graphic control in a form
<b>forma</b>		3		<b>jsp</b>	<b>flabel</b>			<b>forma, formc, formt, formn, formr, jsp, valcons</b>	if there is a form to fill in a JSP, here we indicate the name of a <b>text-area</b> (it is linked to the immediately preceding JSP markup)
<b>formc</b>		3		<b>jsp</b>	<b>flabel</b>			<b>forma, formc, formt, formn, formr, jsp, valcons</b>	if there is a form to fill in a JSP, here you indicate the name of a <b>checkbox</b> (it is linked to the immediately preceding JSP markup)
<b>formn</b>		3		<b>jsp</b>	<b>flabel, fcartel</b>	<b>mybutton, dao, hsqln, ftokens</b>		<b>forma, formc, formt, formn, formr, jsp, valcons</b>	if there is a form to fill in a JSP, here you indicate the name of a <b>list-box</b> (it is linked to the immediately preceding JSP markup)
<b>formr</b>		3		<b>jsp</b>	<b>ftokens, fgroup</b>	<b>fstart, flabel</b>		<b>forma, formc, formt, formn, formr, jsp, valcons</b>	if there is a form to fill in a JSP, here you indicate the name of a <b>radio buttons group</b> (it is linked to the immediately preceding JSP markup)
<b>formt</b>		3		<b>jsp</b>	<b>flabel</b>			<b>forma, formc, formt, formn, formr, jsp, valcons</b>	if there is a form to fill in a JSP, here is the name of a <b>text-box</b> (it is linked to the immediately preceding JSP markup)
	<b>fstart</b>	3		+formr					initial checked option in a radio buttons group
	<b>ftokens</b>	17		+formn, +formr					the list of tokens to fill a dropdown graphic control, or the list of options in a radio button group

MarkupsList-3.3.1.ods

<b>locomotors</b>	<b>wagons</b>	<b>type</b>	<b>frequency</b>	<b>imply</b>	<b>mandatory wagons</b>	<b>optional wagons</b>	<b>domain</b>	<b>previous</b>	<b>description</b>
	<b>goal</b>	13	3	<b>+requmap</b>					the location, path and name, of the destination JSP at the end of this request mapping; if the <i>goal+</i> data is identical to the <i>requmap+</i> data, the <i>goal+</i> markup must be omitted
	<b>hdbms</b>	19		<b>+hdefrail</b>			<b>DB2, MySql, Oracle, Postgres</b>		the DBMS dialect registered in Hibernate
	<b>hdbschema</b>	8		<b>+hdefrail</b>					the DB-schema of the used tables; present as many times as there are DB-schemas
<b>hdefrail</b>		19			<b>hdbschema, hdbms</b>	<b>hjndi</b>	<b>0,1,2,3,4,5,6,7,8,9</b>		data collector of a DB-schema on a database
<b>hjarv</b>		5	3	<b>+hdefrail</b>					the version of the artifact resulting from the build of the JPA jar, in case you want to use a JPA-Maven; is the <version> tag that immediately follows <artifactId>
	<b>hjndi</b>	12		<b>+hdefrail</b>					the name of the data source, one for each DB-schema
	<b>hjpav</b>	19	1	<b>+hv</b>			<b>1,2</b>		version of the JPA
	<b>hrail</b>	2		<b>+utabuser, +qjobname</b>					the identification of the necessary table (railway metaphor)
	<b>hsqln</b>	18		<b>+formn</b>					the SQL query that generates a list-box in a JSP form
<b>hv</b>		5	2		<b>hjpav</b>				short version of the Hibernate framework, no. version consisting of only 2 qualifiers

MarkupsList-3.3.1.ods

<b>locomotors</b>	<b>wagons</b>	<b>type</b>	<b>frequency</b>	<b>imply</b>	<b>mandatory wagons</b>	<b>optional wagons</b>	<b>domain</b>	<b>previous</b>	<b>description</b>
<b>hvalid</b>		5	2	<b>!svalid</b>					validation according to hibernate, different from <i>validator+</i> that validates according to Spring
<b>i18n</b>		3	2	<b>sinterce</b>					internationalization
<b>indexjsp</b>		4	2			bmenu, optioncolor, optionhover, optbackcol1, optbackcol2			presence of a jsp home page
	<b>integer</b>	3	3	<b>+jsp</b>					the list of Integer type properties of the bean associated with the JSP
<b>jacksonver</b>		3	2						version of the Jackson framework
<b>jeev</b>		5	2						Java Enterprise Edition version
<b>jsp</b>		13			belong	bmenu, string, arraystring, integer, long, boolean, dress, cssclass, refresh, pagetitle, crud, blank, legend			path and name of the JSP, the path starts from webapp/WEB-INF/views; only one intermediate directory is allowed
<b>language</b>		3		<b>i18n</b>					language code, it must be 2 characters long
	<b>legend</b>	3		<b>+jsp</b>					parameter for the <legend> tag in the JSP

MarkupsList-3.3.1.ods

<b>locomotors</b>	<b>wagons</b>	<b>type</b>	<b>frequency</b>	<b>imply</b>	<b>mandatory wagons</b>	<b>optional wagons</b>	<b>domain</b>	<b>previous</b>	<b>description</b>
log4j		5	2						Apache Log4j version
long		3	3	<b>+jsp</b>					the list of Long type properties of the bean associated with the JSP
matrix		4	2						presence of matrix variables
mavbu		4	2	mavwa, mavcl, mavcp					if you want the <build> tag in the Maven pom
mavcl		5	2	mavcl, mavwa, mavcp					version of the Maven clean plugin
mavco		5	1						version of java for the Maven compiler
mavcp		5	2	mavbu, mavwa, mavcl					version of the Maven compiler plugin; not to be confused with <i>mavco+</i> , which specifies the Java version
mavgr		3	1						group id by Maven
mavmo		5	1						version of the Maven model
mavwa		5	2	mavbu, mavcl, mavcp					version of the Maven war plugin
method		20	4				<b>dao</b>		Name of the java method; if there is access to the DB in the method, it must be followed by the <i>dao+</i> markup with the list of dao-interfaces accessed by the method
	<b>model</b>	4	3	<b>+requmap</b>					follows, as a wagon, requmap; indicates that the @Controller type class method will have Model model as parameter
mv		5	1						version of Maven

MarkupsList-3.3.1.ods

<b>locomotors</b>	<b>wagons</b>	<b>type</b>	<b>frequency</b>	<b>imply</b>	<b>mandatory wagons</b>	<b>optional wagons</b>	<b>domain</b>	<b>previous</b>	<b>description</b>
	<b>mybutton</b>	3		<b>+formn, +formt, +forma</b>					button located next to a control to immediately send the data online
	<b>ooptbackcol1</b>	7		<b>+bdefmenu</b>					background color no. 1 in the main menu
	<b>ooptbackcol2</b>	7		<b>+bdefmenu</b>					background color no. 2 in the main menu
	<b>obackcolor</b>	7	3	<b>+text, +jsp, cssclass</b>					background color in a CSS
	<b>ocolor</b>	7	3	<b>+text, +jsp, cssclass</b>					text color in a CSS
<b>odefcss</b>		12	4		<b>obackcolor, ocolor, omargin, opadding, ofontsize, oalign</b>				the name of a CSS class to insert in the screwdriver.css file
	<b>ooptioncolor</b>	7		<b>+bdefmenu</b>					text color of the choices on the main menu; when the mouse arrives, color is indicated by ooptionhover+
	<b>ooptionhover</b>	7		<b>+bdefmenu</b>					text color when the mouse hovers the text
	<b>opadding</b>	15	3	<b>+text, +jsp, cssclass</b>					top/bottom padding in the index.jsp
	<b>ofontsize</b>	15	3	<b>+text, +jsp, cssclass</b>					font size of the text of the index.jsp
	<b>omargin</b>	15	3	<b>+text, +jsp, cssclass</b>					margin-top, it is used to pass the eventual menu

MarkupsList-3.3.1.ods

<b>locomotors</b>	<b>wagons</b>	<b>type</b>	<b>frequency</b>	<b>imply</b>	<b>mandatory wagons</b>	<b>optional wagons</b>	<b>domain</b>	<b>previous</b>	<b>description</b>
	<b>oalign</b>	19	3	+text, +jsp, cssclass			left, center, right		x
<b>others</b>		24		+method					list of classes of subsequent arguments of a method (subsequent since they come after the daos)
	<b>pagetitle</b>	3		+jsp					x
	<b>permit</b>	19		+requmap			all, user, admin		x
<b>pompr</b>		2	2						any snippet called within pom.xml, not necessarily properties; you must first insert the various pompr_0.txt, pompr_1.txt, etc. files in the snippets, then recall them with pompr+0, pompr+1, etc.
<b>pragma</b>		4	2	jsp					if I want to check the cache in the previous JSP (corresponds to the immediately preceding jsp + markup)
<b>pretprin</b>		3	2	sv+03.02.00					x
<b>primary</b>		10	2						calling an include file, extension .eli
	<b>qcron</b>	3	2	+qjobname					scheduling in Cron Quartz mode
<b>qjobname</b>		12		quartz	hrail	qcron, qsimple			name of the Quartz job
<b>quartz</b>		5	2	qjobname					Quartz version
	<b>qsimple</b>	3	2	+qjobname					scheduling in Quartz Simple mode



MarkupsList-3.3.1.ods

locomotors	wagons	type	frequency	imply	mandatory wagons	optional wagons	domain	previous	description
	<b>redirect</b>	3		<b>+requmap</b>					in the case of a JSP of the form type, then with a button or another graphic control, it indicates which JSP you go to after clicking on the control
	<b>refresh</b>	2		<b>+jsp</b>					x
<b>requmap</b>		12		<b>jsp</b>		model, permit, goal, redirect			the request mapping that generates a method in a class of type @Controller; it can be multiple, i.e. can indicate a list of paths, all equivalent, separated by commas, which start the method
<b>sdefaulto</b>		19	2				no, byname, bytype, autodetect, constructor		Default-autowire
<b>sieco</b>		14							in MVC: view-controller, it represents both the path and the view-name
<b>sinterce</b>		12							class subjected to interceptor; no extension must be specified
<b>sreso</b>		16							in the DispatcherServlet, write a <mvc:resources tag for each sreso: resource of the type /resources/xxxxyyyy/**, the mapping is this location + 2 asterisks
<b>srobo</b>		12	2						in the DispatcherServlet: presence of the typical Spring robots.txt file
	<b>string</b>	3	3	<b>+jsp</b>					the list of String type properties of the bean associated with the JSP
<b>sv</b>		5	1	<b>primary</b>					Spring version
<b>svalid</b>		4	1	<b>!hvalid</b>					I want data validation according to Spring

MarkupsList-3.3.1.ods

locomotors	wagons	type	frequency	imply	mandatory wagons	optional wagons	domain	previous	description
text		3	2	indexjsp	cssclass				text of index.jsp
uintp		12		uv					properties files internal to the war, specific for Spring Security
	upassword	12	2	+utabuser					column of the users table containing the password
userpass		21	2	uv		bmenu	simple, domain, trivial		if I want an independent JSP with userid and password, and all the consequent treatment; the value is <b>simple</b> if I only have userid and password, <b>domain</b> if I also have the network domain; <b>trivial</b> when the userid and password are specified in clear text in the XML file that manages the Authentication Manager
uspaformadmin		3	2	userpass+trivial					userid and password (separated by commas) in the trivial case of userid and password carved in the code, case ROLE_ADMIN
uspaformuser		3	2	userpass+trivial					userid and password (separated by commas) in the trivial case of userid and password carved in the code, case ROLE_USER
usignup		4	2	userpass					if you want to add a new user registration functionality to the application; the menu item is simply added, but then the JSP must be added with all its management
utabuser		12	2	userpass	hrail, uwelcome, upassword				name of the table containing the user's profile
uv		5	2	sv, xprovider					security version, is absent if spring security is not used

MarkupsList-3.3.1.ods

locomotors	wagons	type	frequency	imply	mandatory wagons	optional wagons	domain	previous	description
	<b>uwelcome</b>	12	2	+utabuser					column of the users table that must appear after the login with the welcome
<b>valcons</b>		19		defaulan	valtag	valparams	@AssertFalse, @AssertFalse.List, @AssertTrue, @AssertTrue.List, @DecimalMax, @DecimalMax.List, @DecimalMin, @DecimalMin.List, @Digits, @Digits.List, @Future, @Future.List, @Max, @Max.List, @Min, @Min.List, @NotEmpty, @NotNull, @NotNull.List, @Null, @Null.List, @Past, @Past.List, @Pattern, @Pattern.List, @Size, @Size.List	<b>forma, formt, formc</b>	validation constraints (JSR 303 Bean Validation)
<b>vallabel</b>		3		defaulan	valmess	vallang			defines a label for a validation message with negative result
	<b>vallang</b>	23		+vallabel					the language code for that message
	<b>valmess</b>	3		+vallabel					message corresponding to the label
	<b>valparams</b>	3		+valcons					parameters used to declare a validation constraint
	<b>valtag</b>	3		+valcons					label of the validation message
<b>weberror</b>		4	2						presence of error-page parameters in web.xml
<b>webmime</b>		4	2						presence of mime-mapping parameters in web.xml

MarkupsList-3.3.1.ods

locomotors	wagons	type	frequency	imply	mandatory wagons	optional wagons	domain	previous	description
wparams		3							web flow framework parameters
wv		5	2						version of the web flow framework
xauth		18	2	xprovider+jdbc, !xgbac					select SQL query, select individual permissions
xencoder		19	2	xprovider			useridMD5, saltedsha256		it is the type of hash + salt of the password, to be set on the DB for comparison; allowed values: saltedsha256 if xprovider = jdbc; useridMD5 if xprovider = class
xlbase		12	2	xprovider+ldap					the user group is specified, through group-search-base
xlclass		3	2	xprovider+ldap					indicates the class of LDAP users, in the <a href="#">user-details-class</a> parameter in security.xml
xlpass		12	2	xprovider+ldap					specify the treatment of the password in LDAP: it can have as argument <b>password-compare</b> , <b>hash_ssh</b> , or any other value, present in the LDAP configuration, to be used as <b>password-attribute</b>
xlservice		4	2	xprovider					you want to use LdapUserDetailsService
xgbac		18	2	xprovider+jdbc, !xauth, !xusers					select SQL query, select user groups
xprovider		19	2	uv			user-service, class, jdbc, ldap		Authentication Provider methodology, element of Spring Security
xusers		18	2	xprovider+jdbc, !xgbac					select SQL query, select individual users

MarkupsList-3.3.1.ods

<b>locomotors</b>	<b>wagons</b>	<b>type</b>	<b>frequency</b>	<b>imply</b>	<b>mandatory wagons</b>	<b>optional wagons</b>	<b>domain</b>	<b>previous</b>	<b>description</b>
<b>Markup to be used internally in an .eli file</b>									
<b>colorform</b>		7	2	<b>userpass</b>					color of the area around the login button
the data types of the markups are:									
1 = a date, mandatory									
2 = an unsigned non negative integer number									
3 = a string of at least 1 character, mandatory									
4 = no parameters									
5 = a software release, mandatory									
6 = a string, optional									
7 = a CSS color									
8 = like 12, and automatically converted to lower case									
9 = like 4, but to be found among the includes									
10 = like 3, but to be found among the includes									
11 = like 5, but to be found among the includes									
12 = like 3 but composed of a single word; it can be a path without spaces									
13 = a string of a path plus file name, not more than 1 slash									

MarkupsList-3.3.1.ods

<b>locomotors</b>	<b>wagons</b>	<b>type</b>	<b>frequency</b>	<b>imply</b>	<b>mandatory wagons</b>	<b>optional wagons</b>	<b>domain</b>	<b>previous</b>	<b>description</b>
14 = like 13 but optional									
15 = an integer with or without sign, mandatory									
16 = a one-word string, but optional									
17 = a string composed of substrings separated by commas, mandatory									
18 = a string consisting of a select SQL, mandatory									
19 = a string, mandatory one of the values declared in the "domain" column									
20 = precedes the text of a file or source code									
21 = like 19, but to be found among the includes									
22 = like 17, but optional									
23 = a language code, ISO 639-1									
24 = like 17, but substrings must be composed by one word									
The frequencies are:									
0 = it doesn't matter									
1 = once and only once (only 1)									
2 = no more than once (0 or 1)									
3 = at least once (> 0)									
4 = it doesn't matter, but without identical repetitions									
5 = at least once, but without identical repetitions									